

## 1. IDENTIFICATION

**Product Identifier****Product Name** Slide Hi-Temp 1800 Mold Release**Other means of identification****SDS #** 44110**Product Code** 44110**UN/ID No** UN1950**Recommended use of the chemical and restrictions on use****Recommended Use** Industrial mold release.**Details of the supplier of the safety data sheet****Supplier Address**Slide Products Inc.  
430 S. Wheeling Road  
Wheeling, IL 60090**Emergency Telephone Number****Company Phone Number**

Phone: 1-847-541-7220

Fax: 1-847-541-7986

**Emergency Telephone (24 hr)**

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Clear, oily, colorless liquid**Physical State** Aerosol**Odor** Slight ethereal**Classification**

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Flammable Aerosols	Category 2

**Signal Word****Danger****Hazard Statements**

Harmful if inhaled

Causes serious eye irritation

Flammable Aerosol



**Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear eye/face protection  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a poison center or doctor/physician  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a poison center or doctor/physician if you feel unwell

**Precautionary Statements - Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Dimethyl ether	115-10-6	40-50
1,1 difluoroethane	75-37-6	40-50
Isopropanol	67-63-0	8-12
Butyl acetate	123-86-4	<2

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

**First Aid Measures**

<b>Eye Contact</b>	Rinse thoroughly with plenty of water, also under the eyelids. Immediately call a poison center or doctor/physician.
<b>Skin Contact</b>	Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
<b>Ingestion</b>	Do not induce vomiting. If conscious, give 1 glass of water or milk to dilute. Call a physician or poison control center immediately.

**Most important symptoms and effects**

<b>Symptoms</b>	Causes serious eye irritation. Exposed individuals may experience eye tearing, redness and discomfort. Concentrated spray may cause freezing of skin area. Skin contact can lead to drying, defatting, itching, stinging and irritation. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. Irritating to mouth, throat, and stomach if ingested.
-----------------	---

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical.

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

This product is a flammable aerosol. Aerosols may rupture violently at temperatures above 120 F. Pressurized container: May burst if heated.

**Hazardous Combustion Products** Carbon oxides.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Use personal protective equipment as required.

**Environmental Precautions** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

### Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Clean-Up** Keep in suitable, closed containers for disposal.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on Safe Handling** Wash thoroughly after handling. Use personal protection recommended in Section 8. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not drop.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Incompatible Materials** Strong oxidizers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>

### Appropriate engineering controls

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits.

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses.

**Skin and Body Protection** Wear suitable protective clothing.

**Respiratory Protection** Ensure adequate ventilation, especially in confined areas.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Aerosol	<b>Odor</b>	Slight ethereal
<b>Appearance</b>	Clear, oily, colorless liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Clear Colorless	<b>Remarks • Method</b>	
<b>Property</b>	<b>Values</b>		
<b>pH</b>	Not determined		
<b>Melting Point/Freezing Point</b>	< -45 °C / <-50 °F		
<b>Boiling Point/Boiling Range</b>	Not available		
<b>Flash Point</b>	Not available		
<b>Evaporation Rate</b>	Extremely rapid		
<b>Flammability (Solid, Gas)</b>	Flammable aerosol		
<b>Upper Flammability Limits</b>	25.0%		
<b>Lower Flammability Limit</b>	4.0%		
<b>Vapor Pressure</b>	Not available		
<b>Vapor Density</b>	Not available		
<b>Specific Gravity</b>	1.0	(Water = 1)	
<b>Water Solubility</b>	Partially soluble		
<b>Solubility in other solvents</b>	Not determined		
<b>Partition Coefficient</b>	Not determined		
<b>Auto-ignition Temperature</b>	Not determined		
<b>Decomposition Temperature</b>	Not determined		
<b>Kinematic Viscosity</b>	Not determined		
<b>Dynamic Viscosity</b>	Not determined		
<b>Explosive Properties</b>	Not determined		
<b>Oxidizing Properties</b>	Not determined		
<b>Bulk Density</b>	8.37 lb/gal @ 60°F		

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization**      Hazardous polymerization does not occur.

### Conditions to Avoid

Do not puncture or incinerate cans. Avoid temperatures above 120 °F.

### Incompatible Materials

Strong oxidizers.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

**Eye Contact**                      Causes serious eye irritation.

**Skin Contact**                     Avoid contact with skin.

**Inhalation**                         Harmful if inhaled.

**Ingestion**                         Do not ingest.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dimethyl ether 115-10-6	-	-	= 308.5 mg/L ( Rat ) 4 h
Isopropanol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rat ) = 12870 mg/kg ( Rabbit )	= 72.6 mg/L ( Rat ) 4 h
Polyacrylic acid 9003-01-4	= 2500 mg/kg ( Rat )	-	-
Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 391 ppm ( Rat ) 4 h

### Information on physical, chemical and toxicological effects

**Symptoms**                         Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Carcinogenicity**

Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropanol 67-63-0		Group 3		X
Polyacrylic acid 9003-01-4		Group 3		

**Legend****IARC (International Agency for Research on Cancer)**

Group 3 IARC components are "not classifiable as human carcinogens"

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Isopropanol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50		13299: 48 h <i>Daphnia magna</i> mg/L EC50
Polyacrylic acid 9003-01-4		580: 96 h <i>Lepomis macrochirus</i> mg/L LC50		168: 96 h water flea mg/L EC50
Butyl acetate 123-86-4	674.7: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	17 - 19: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 100: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 62: 96 h <i>Leuciscus idus</i> mg/L LC50 static	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	72.8: 24 h <i>Daphnia magna</i> mg/L EC50

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
Dimethyl ether 115-10-6	-0.18
Isopropanol 67-63-0	0.05
Butyl acetate 123-86-4	1.81

**Other Adverse Effects**

Not determined

**Ozone**

Contains no ozone depleting chemicals

**13. DISPOSAL CONSIDERATIONS****Waste Treatment Methods**

<b>Disposal of Wastes</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated Packaging</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Isopropanol 67-63-0	Toxic Ignitable
Butyl acetate 123-86-4	Toxic

**14. TRANSPORT INFORMATION****Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. **Based on package size, product may be eligible for limited quantity exception.**

**DOT**

<b>UN/ID No</b>	UN1950
<b>Proper Shipping Name</b>	Aerosols
<b>Hazard Class</b>	2.1

**IATA**

<b>UN/ID No</b>	UN1950
<b>Proper Shipping Name</b>	Aerosols, flammable
<b>Hazard Class</b>	2.1

**IMDG**

<b>UN/ID No</b>	UN1950
<b>Proper Shipping Name</b>	Aerosols
<b>Hazard Class</b>	2.1

**15. REGULATORY INFORMATION****International Inventories**

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Dimethyl ether	Present	X		Present		Present	X	Present	X	X
1,1 difluoroethane	Present	X		Present		Present	X	Present	X	X
Isopropanol	Present	X		Present		Present	X	Present	X	X
Butyl acetate	Present	X		Present		Present	X	Present	X	X

**Legend:***TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances**AICS - Australian Inventory of Chemical Substances***US Federal Regulations****CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	67-63-0	10	1.0

**CWA (Clean Water Act)**

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate	5000 lb			X

**US State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Dimethyl ether 115-10-6	X	X	X
1,1 difluoroethane 75-37-6	X	X	
Isopropanol 67-63-0	X	X	X
Butyl acetate 123-86-4	X	X	X



<b>16. OTHER INFORMATION</b>
------------------------------

**NFPA****Health Hazards****Flammability****Instability****Special Hazards**

Not determined

Not determined

Not determined

Not determined

**HMIS****Health Hazards****Flammability****Physical Hazards****Personal Protection**

1

3

0

B

**Issue Date:** 01-Sep-2012**Revision Date:** 01-Jan-2015**Revision Note:** New format**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**